

HELICOPTER SOLUTIONS

THE PROOF IS IN THE PERFORMANCE



GARMIN®



CONTENT

GI 275 Electronic Flight Displays	05
G500H TXi Flight Display	06
HSV™ Synthetic Vision Technology	07
GTN™ Xi Series Navigators	08
Terrain Awareness and Warning System	10
GFC™ 600H Flight Control System	11
GNC™ 215/GTR™ 205 NAV/COMM Radios	12
GMA™ Series Digital Audio Control	12
Flight Stream 210/510 Wireless Gateways	13
SiriusXM® Satellite Weather	14
GSR 56H Global Weather/Voice/Text	14
GTS™ Series Active Traffic	14
ADS-B Solutions	15
GTX™ Series All-in-one ADS-B Transponders	16
GDL® Series ADS-B Datalinks	16
GWX™ 75H Digital Weather Radar	17
GRA™ 55 Radar Altimeter	18
Garmin Services	19
Product Specifications	20

PUT BETTER DECISION-MAKING TOOLS AT YOUR FINGERTIPS WITH GARMIN HELICOPTER AVIONICS

The versatility that helicopters bring to the world of aviation is reflected in the wide range of missions they fly: emergency medical services, law enforcement, offshore logistics, search and rescue, aerial touring, heavy-lift, executive transport, pilot training and many more. Each has its own operational challenges. And for some, these challenges have grown — as busier airspace and ever-more-demanding flight environments have increased the focus on safety, industry wide. An FAA task force identified three primary areas where operational risks for helicopters need special attention: 1) inadvertent flight into instrument meteorological (IMC) conditions, 2) night operations, and 3) controlled flight into terrain (CFIT). Many ongoing studies have reinforced these findings. And in response, many operators are now asking for technologies that can proactively (and affordably) help them address these safety issues.

To that end, Garmin is focusing our decades of experience in aviation safety-enhancing technology on the specialized needs of today's helicopter community. And we're proud to offer a robust array of systems and solutions designed specifically for helicopters — many of which you'll find featured on these pages. Whether it's high-resolution terrain/obstacle graphics with HTAWS alerting and voice call-outs of altitude when descending below 500', or worldwide datalink weather with NEXRAD imagery or all-digital radar altimetry or HSVT™ synthetic vision technology that renders terrain-alerting data into a realistic 3-D "virtual reality" landscape on the primary flight display — whatever it takes, just know that Garmin is serious about helicopter safety.



GI 275 ELECTRONIC FLIGHT DISPLAYS

Approved for STC installation in select Part 27 helicopters, the GI 275 electronic flight instrument makes it easy to replace maintenance-prone, vacuum-driven gauges in your panel with cost-effective, dependable ADAHRS-driven electronics. It's designed to flush mount in an existing 3-1/8" standard cutout with little or no panel modification required — keeping installation time and expense to a minimum.

The instrument can be configured as a direct replacement for primary reference for your attitude indicator, HSI, CDI or radar altimeter display. It can also function as an MFD or standby flight instrument. The modular "building block" design lets you start with one unit, then add additional units to provide added functionality and redundancy to your system as your needs evolve.

MORE FLIGHT DATA. AT A GLANCE.

With the capability to combine attitude, altitude, airspeed, heading and vertical speed reference, the GI 275 attitude indicator makes critical flight information easier and faster to scan. To add further situational awareness, it can optionally incorporate Garmin HSVT™ 3D synthetic vision, enabling you to clearly envision your flight situation in perspective.

NAVIGATE WITH ENHANCED HSI

For added directional reference, appropriate NAV inputs let you configure GI 275 as an HSI with course guidance overlaid on a moving map display — showing flight plan legs, terrain, wires, obstacles, weather and more. Alternatively, a built-in VFR GPS receiver enables convenient Direct-to guidance to selected waypoints, with your position depicted on the moving map display.

SEE MORE INFORMATION. NOT MORE SCREENS.

Configured as an MFD, GI 275 offers such functions as moving map, WireAware™ wire-strike avoidance technology, traffic, weather, terrain and more¹. Optional HTAWS is available when installed with your compatible HTAWS-enabled navigation source, such as the GNS™ series, GTN™ series and GTN™ Xi series navigators². And for applications that require precise tracking of aircraft altitude above the terrain, GI 275 can be installed as a dedicated display for select radar altimeters, including the GRA™ series.

Plus, GI 275 uses built-in Connex[®] wireless cockpit connectivity to stream traffic, weather, GPS position and ADAHRS reference data from your avionics to your compatible mobile device running with the Garmin Pilot™, ForeFlight or FltPlan Go apps — essentially turning your compatible tablet into a portable navigation display and cockpit interface.

¹Weather and traffic information requires compatible datalink source (sold separately) • ²Navigator must have HTAWS enabled





G500H TXi FLIGHT DISPLAY

Providing our latest in electronic glass cockpit instrumentation on bright, crisp 10.6" and 7" LCD touchscreen displays, Garmin G500H TXi brings new levels of reliability, adaptability and affordability to helicopter operations. The displays' clean-sheet design, dual-core processing power and proven ADAHRS attitude/heading reference all build on the proven capabilities of our original G500H series to offer a vastly expanded array of features, options and panel layout possibilities. The 10.6" horizontal format can accommodate primary flight display (PFD) information and a multifunction display (MFD) side-by-side within the same unit. The display is pilot-selectable for PFD or PFD/MFD presentation. And the PFD/MFD option is configurable, allowing it to be split 60% PFD and 40% MFD — or 40% PFD and 60% MFD to allocate more room for maps or other features you want to see most prominently. Similarly, the 7" portrait format displays can be individually dedicated to PFD (with HSI map) or MFD functions. Another option, where panel space is limited, allows the 7" landscape format display to serve



Compared to the 3-color shading graphics used for fixed-wing Terrain Proximity displays, the crisp 5-color shading scheme featured on Garmin helicopter systems yields additional elevation reference data for pilots who routinely fly lower and closer to the ground.

as a dedicated PFD with instrument tapes, a half-arc HSI and our optional Garmin HSVT™ 3-D synthetic vision. For added situational reference, the display puts an MFD-like perspective map view within the HSI portion of your PFD. In addition to the geographical map, the HSI map view can also support the overlay of NEXRAD imagery and weather inputs from ADS-B and SiriusXM® datalinks. Additional overlays include SafeTaxi® airport diagrams, WireAware™ power line avoidance, traffic, terrain and more. HSI map control and on-screen navigation are a snap, thanks to a Garmin innovation that lets you zoom in or out on the map by using a simple and natural single-finger swipe gesture. Plus, the TXi screens are also provisioned for night vision goggle (NVG) compatibility. And to further reduce pilot workload, G500H TXi offers full integration with the Garmin GFC 600H digital flight control system, as well as other Garmin or 3rd party navigators, radios, and related equipment. There are also multiple input options that enable the TXi multifunction display to serve as a FLIR, live-cam monitor or other video source*.


For added versatility and convenience, G500H TXi lets you use familiar knobs and/or touchscreen inputs to quickly access the functions, screen views and other flight information you want to see. When paired with our GTN™ 750Xi/650Xi series GPS navigators, the G500H displays provide full touchscreen continuity between the navigation, communication and flight display functions in your helicopter.



Providing multiple inputs for optional video, G500H TXi supports a variety of camera configurations and locations — enabling the MFD to function as a FLIR, tail-cam or live video monitor.



Garmin WireAware™ wire-strike avoidance technology combines with optional HTAWS terrain alerting to provide a comprehensive hazard avoidance solution for low-level helicopter operations.



With navigation inputs, G500H TXi can put an MFD-like perspective map view within the HSI portion of your primary flight display. This HSI map can incorporate NEXRAD imagery and weather data as well as SafeTaxi® diagrams, traffic, terrain alerting and more.

*Database currently covers North America and Western Europe only.

HSV™ SYNTHETIC VISION TECHNOLOGY

Specially adapted to the needs of helicopter operators, Garmin's HSVT synthetic vision technology brings a unique graphical perspective to "glass cockpit" instrumentation. Available on G500H TXi as an option, HSVT can make a world of difference when visibility deteriorates. Using sophisticated computer modeling to recreate a virtual topographic landscape from the system's terrain-alerting database, HSVT gives helicopter pilots a clear depiction of ground and water features, airports, obstacles, traffic and more — all shown in 3-D perspective on the primary flight display. Garmin's HSVT graphics look so real, it's almost like having a clear-day "out-the-window" view of your flight situation — even in the dark nighttime VFR or other degraded visibility environments (DVE). Although synthetic vision is not intended to replace traditional attitude and directional cues as one's primary flight reference, it clearly does augment the pilot's view of this data, by giving it a realistic visual frame of reference. For example, when flying in areas where rising terrain may pose a hazard, Garmin HSVT uses its database to "paint" the landscape with amber or red overlays showing where potential CFIT risks exist. As with Garmin's HTAWS alerting, this HSVT "paint" feature offers user-selectable Reduced Protection to accommodate low-level operations without excessive terrain alerts. Towers or obstacles that may encroach upon one's flight path are also color-highlighted with hazard-appropriate symbology. So, when it comes to maintaining situational awareness, it's easy to see that Garmin HSVT is great technology to have.



Operations into unfamiliar airports are easier with Garmin HSVT. Airport identifiers, runway surfaces, numbers and thresholds are all clearly depicted.



Garmin HSVT helps pilots look out for non-terrain structural hazards. Color-coded 3-D symbols show structures that may encroach the flight path.



3-D traffic depiction on HSVT helps pilots see if traffic targets are above or below their altitude. As intruders get closer, the symbols get larger.



The Garmin GTN Xi Series of touchscreen avionics are provisioned to enable helicopter pilots to join their fixed-wing counterparts in the world of WAAS/SBAS navigation. These satellite “augmentation” systems use enhanced GPS signals to enable IFR flight and vertical glidepath approaches into non-ILS-equipped runways and heliports. A special helicopter-specific Garmin aviation database lets GTN Xi operators easily navigate to more than 7,000 heliports, without having to create their own user waypoints at those locations. What’s more, on the comm side, a helpful recall function allows often-used radio frequencies to be stored in memory for quick access during flight. An optional switch on the control stick enables pilots to remotely select from these stored frequencies – and activate them via “flip-flop” entry – without removing their hands from the flight controls.

GTN™ Xi SERIES TOUCHSCREEN AVIONICS

Combining our latest in moving map and graphical features with touchscreen data entry and integrated radio tuning, the new-generation Garmin GTN Xi series brings unprecedented levels of convenience, efficiency and situational awareness to the helicopter industry’s latest GPS/Nav/Comm/MFD suite.

To maximize space-limited avionics stacks, the compact GTN 650Xi model fits in a 2.65" tall slot – while the GTN 750Xi bezel stands 6" high and features an MFD-like 6.9" display. Both versions meet stringent environmental and vibration standards for helicopters. And configurations with built-in, night-vision goggle compatibility are also available.

Featuring high-speed processors that cut boot-up time by up to 50% over earlier GTN models, the GTN Xi series provides quick access to frequencies, flight plan data, database updates and more. The added processing power also supports faster graphics rendering and smoother panning, plus convenient smartphone-like swipe and pinch-to-zoom gestures to align and scale the map view on the screen. The super high-resolution display has a wider viewing range and almost double the pixel count of earlier GTN models – making it one of our highest-resolution displays ever offered in this class of avionics.

Incorporating a complete range of GPS- and VHF-guided navigation capabilities, the GTN Xi series makes it easy to create routes, load flight plans and fly all types of arrival, departure and approach procedures. The SBAS/WAAS-certified navigator allows you to fly GPS-guided LPV glidepath instrument approaches down to as low as 200', greatly expanding your low-visibility landing options. What’s more, when operating in VFR conditions, the GPS can also provide advisory vertical approach guidance based either on a published glidepath angle or by generating a 3-degree vertical flight path from the runway threshold down to pilot-selectable minimums – while taking terrain and obstacle clearance into account. With this advisory guidance, you’re able to fly more consistent and more precise vertical glidepaths into any airport published in the database.

To further simplify navigation, you can easily transfer several common waypoints at a time, using the SD card slot or by directly entering them via multiple common lat/long formats or VOR radials. These can be marked as airports to help limit excessive terrain alerts.

For added awareness against powerline incidents, WireAware™ wire-strike avoidance technology is an available option. The basic helicopter database includes all hazardous obstacle transmission, or HOT, lines that span rivers and canyons in areas that can prove treacherous to low-flying pilots. With WireAware these lines are clearly identified on the map page, with detailed information (including MSL and AGL line heights) available at the press of each wire segment on the display. For even more awareness, adding HTAWS to the system enables both audible and visual alerting to call attention to wire hazards in proximity to the flight path.

Easily integrated with other Garmin avionics, the GTN Xi series can support a wide array of optional weather, lightning and traffic system inputs for overlay on the moving map – as well as exclusive workload-reducing features such as Telligence™ voice command technology.

If your mission calls for search and rescue operations, GTN Xi provides an optional selection of four common search pattern types (Orbit Search, Parallel Line Search, Expanding Square and Sector Search) for easy entry into your flight plan. Other features include FastFind predictive logic to suggest airport and waypoint entries using current GPS position; streamlined frequency entry; customizable checklists; airspace altitude overlays on the moving map page; shortcut access to frequently used data fields, functions, pages, and more. The GTN 750Xi and 650Xi series can provide control/display for optional remote-mount transponders. And the larger GTN 750Xi series also offers support for optional remote audio panel control.

When installed with remote switches on the cyclic or collective, the GTN Xi series can further help reduce cockpit workload by allowing pilots to create flyover mark-on-target waypoints or remotely tune frequencies, all without letting go of the controls. Additionally, other key GTN Xi interfaces can support TAS/TCAS traffic systems, datalink weather and radar altimeter inputs for enhanced HTAWS alerting. In effect, these multiple interface options let pilots utilize the GTN Xi touchscreen as a virtual flight management system.

Then, for even more touchscreen convenience, you can add a Garmin Flight Stream wireless gateway¹ to your system, enabling select Connex-capable apps such as Garmin Pilot™ – as well as aviation portables from our aera® series – to stream data to/from your GTN Xi series avionics via a Garmin Connex® link. With Connex onboard, you can preload flight plans – including your own waypoints – onto your iPad® (or other compatible device) for quick and easy uploading into your avionics. And you can also use the Connex wireless connectivity to load and keep all your databases in sync with Database Concierge automatic updating. Additionally, the link provides more robust GPS position data (streamed from the GTN Xi) for apps such as Garmin Pilot and FltPlan Go on your device, as well as the option to display weather, traffic and backup attitude information – so your tablet essentially becomes an extra control/display in the cockpit.




¹Sold separately. Capabilities such as GPS, attitude, weather, traffic and flight plan transfer, SiriusXM® weather and audio control are limited to the version of Flight Stream, the avionics installed in the aircraft, as well as the portable device. Compatibilities continue to grow with more apps and Garmin portables. Check the Flight Stream page’s [Supported Devices](#) tab for the latest feature and compatibility information.

iPad, iPhone and Apple are trademarks of Apple Inc., registered in the U.S. and other countries. Sirius, XM and all related marks and logos are trademarks of Sirius XM Radio Inc.



Garmin HTAWS terrain alerting, designed specifically for helicopters, is optionally available with Garmin GTN 750 Xi and GTN 650 Xi touchscreen avionics. It's also available as an upgrade to existing GTN Xi series and GNS 530W/430W series navigators. It uses an expanded database containing over 30,000 more structures, obstacles and oil rigs than the Garmin fixed-wing aviation versions.



Garmin WireAware™ technology combines with optional HTAWS (Helicopter Terrain Awareness and Warning System) data to provide a comprehensive hazard and wire-strike avoidance solution. The basic helicopter obstacle database includes all identified hazardous obstacle transmission (HOT) lines — typically those that span rivers, canyons, valleys, etc. — with AGL/MSL elevation provided on individual line segments. Coverage includes the U.S., as well as some power distribution lines in Canada and Mexico.

HTAWS TERRAIN ALERTING OPTION

Providing visual and aural advisories to help keep pilots separated from hazardous terrain, this safety-enhancing technology is engineered specifically for helicopter flight regimes. When optionally installed in select Garmin WAAS/SBAS GPS navigators, the HTAWS offers “forward looking” terrain avoidance (FLTA) capability to predict in advance where potential hazards may exist — and allow time for the pilot to take corrective action. WAAS/SBAS GPS position information is compared with the navigation system's internal terrain/obstacles/airport databases to determine conflict scenarios. If one's helicopter has inadequate terrain and/or obstacle clearance ahead, based on the system's projected flight path, HTAWS caution and warning alerts are issued to the pilot. Accompanying FLTA voice alerts also indicate the relative threat level, with messages such as “Caution, Obstacle, Obstacle” or “Warning, Terrain, Terrain.” In addition to terrain and obstacle alerting (with 5-color Terrain Proximity display for helicopters), Garmin HTAWS also features voice call-outs, or VCOs, which audibly announce the helicopter's height above terrain when descending below 500'. VCO altitude call-outs operate in all HTAWS modes, and Garmin



technology allows the pilot to select multiple call-out menus, in 100' intervals, descending from 500' down to 100' (or down to 50' with an installed GRA 55 radar altimeter). To minimize “nuisance” alerts, Garmin HTAWS offers pilot-selectable options to: 1) suppress an active audible caution alert (while still displaying visual annunciations), or 2) use a “reduced protection” or “RP” mode, which allows for low-level operations and off-airport landings with reduced alerting, while continuing to provide protection from terrain and obstacles. A third option inhibits HTAWS alerting altogether — but still allows voice call-outs to audibly announce the aircraft's height above terrain when descending to 500' or below. Garmin developed a special helicopter obstacle database for its HTAWS option, adding more than 30,000 lower-height structures to its existing software — and enabling the system to depict some 25% more obstacles that might pose a hazard to helicopter operations. Customers with existing Garmin GTN Xi or GNS 530W/430W series navigators may opt to easily upgrade their units with HTAWS capability by contacting an Authorized Garmin Service Center for an on-site upgrade.

GFC™ 600H FLIGHT CONTROL SYSTEM

For helicopter operators, the GFC 600H represents a breakthrough in cost-effective, safety-enhancing technology that can help reduce pilot workload, fatigue and stress levels in busy airspace or marginal weather conditions. Advanced AHRS-based flight control reference, developed by Garmin, combines with redundant cross-checking sensors and robust “smart” servos to provide a superior level of smoothness, precision and response. The system's advanced digital automation features include attitude hold with speed stability, hover assist, overspeed and low speed protection, automatic LVL mode and more. Plus, cyclic-mounted controls allow easy engagement of the flight control system and its primary functions without taking a hand off the controls or going “eyes-down” in the cockpit.

The GFC 600H system's architecture supports full pitch-and-roll axis control capabilities, plus an available 3rd axis servo can provide for optional yaw damp capability — supplementing tail rotor pedal input by the pilot to help maintain heading and keep the helicopter in smooth, coordinated flight. The system can operate as a stand-alone flight control system or easily integrate with a variety of Garmin flight displays and navigation sources (as well as third-party equipment) for additional capability. When appropriately equipped, the GFC 600H can be configured to a 4-axis, IFR-capable system to also include advanced safety features such as power limiting and low-height protection.

For procedures such as visual approaches, the system can use guidance from a compatible WAAS-enabled navigation source — such as our GTN™ Xi series or G1000 NXi flight deck — to automatically fly the helicopter along a desired lateral and vertical flight path. The attitude hold (ATT) mode, activated via the mode controller or cyclic-mounted control, will maintain the commanded pitch, roll or heading; however, while activated, the pilot can easily “fly through” the flight control inputs for smooth hand-flown maneuvers. Another safety-enhancing feature, standard with GFC 600H, is our Helicopter Electronic Stability and Protection system, or H-ESP™. This technology serves to help the pilot easily maintain safe attitude and speed limits when hand-flying the helicopter. H-ESP functions independently of the system — although it uses the same control servos — to assist in maintaining a safe, stable flight condition whether the system is engaged or not. To further help enhance safety in potentially disorienting situations, a dedicated level mode (LVL) can be engaged by the pilot to automatically initiate recovery from unusual attitudes and return the helicopter to straight-and-level flight. As needed, H-ESP can be disabled manually to allow for tactical flight maneuvers. And when the system detects that you're hovering, the innovative hover assist feature will automatically provide flight control inputs to help maintain that position over the ground. It will also hold heading in hover when equipped with the optional yaw axis control. Supplemental type certification for 3-axis, VFR GFC 600H systems is available for AS350 BA, B2/B3, B3E and Bell 505. Four-axis, IFR GFC 600H systems are currently available in select new production helicopters.



Garmin H-ESP™ (Helicopter Electronic Stability and Protection) comes standard with the GFC 600H flight control system. Using the servos of the GFC 600H, H-ESP applies a corrective force on the controls to assist the pilot in maintaining the aircraft in a safe, flight-stable condition whenever pitch, roll or speed deviations exceed the recommended limits.



The Garmin GNC 215 series NAV/COMM radios offer full 200-channel VOR/LOC/GS capability and 10 watts of COMM transmit power — or 16 watts with optional enablement. The companion GTR 205 series COMM-only transceiver offers the same choice of VHF power output configurations. And both the GNC and GTR radios are available with pilot-selectable 25 or 8.33 kHz spacing — providing up to 2,280 channels with 8.33 spacing to meet the COMM compliance rules for Europe.

GNC® 215/GTR™ 205 NAV/COMM RADIOS

The GNC/GTR series of radios bring whole new levels of efficiency and convenience to helicopter cockpit management, while also offering a slimline design, intuitive controls and bright, full-color LCD displays.

The units’ handy frequency-lookup function allows you to simply enter the navaid or airport identifier to find the frequency (or frequencies) from their built-in worldwide databases. Plus, when paired with your compatible GPS source,

they offer reverse frequency lookup to find NAV and COMM frequencies for the nearest stations and automatically display the station identifier and type once you’ve tuned to a frequency (TWR, ATIS, ACC and more) so you can easily verify who you’re talking to.

Frequency presets, which can be accessed via a remote switch, enable you to tune a COMM frequency into the standby display and then activate it via “flip-flop” entry — without removing

your hands from the flight controls. Standby COMM frequency monitoring enables you to listen to ATIS or other transmissions without leaving the active frequency.

Other handy features include a built-in course deviation indicator (CDI) on the NAV side, standby VOR frequency monitoring with a display of the received radial, automatic storage for the last 20 COMM frequencies you’ve called and storage/recall for up to 20 of your most often-used frequencies.



GMA™ SERIES DIGITAL AUDIO CONTROL

Advanced audio switching technology from Garmin can do even more to help you stay focused on flying when things get busy in the cockpit. With the helicopter-robust GMA 350Hc digital audio panel, a patented Telligence™ voice control feature lets you activate certain key audio functions by using spoken commands. So, you can simply press a push-to-command button on the handgrip and say “Comm One” (or Two, or whatever) to select the radio you want — all without lifting a finger from the controls.

You can also verbally select the call playback mode: Just say “Read back” to get an instant replay of the last ATC transmission. Plus, our unique “3-D Audio” technology works to spatially separate inputs coming into each headset — helping you identify which ones to focus on. This 3-D audio capability is also available on the GMA™ 345 audio panel. This Bluetooth®-enabled unit combines rich “home theater” quality sound with wireless connectivity that makes it easy for you to pair your smartphone or other compatible

device with the audio system — so you can make and receive calls in the cockpit, as well as stream audio entertainment through your headsets. Both the GMA 350Hc and GMA 345 audio panels include ambient noise level sensing for enhanced auto-squelch. The GMA 350Hc adds night vision goggle (NVG) compatibility with green annunciation and backlighting — plus it offers three-comm radio support and corresponding split-comm modes (1/2, 1/3 or 2/3) to accommodate a third radio.

With Garmin 3-D audio processing, sound reception in your stereo headset can have a directional effect. For example, Comm 1 may sound as if it’s coming from your 11 o’clock position; Comm 2 from your 1 o’clock; copilot intercom from 3 o’clock and so on. The 3-D feature can be enabled/disabled to suit your preference.



FLIGHT STREAM WIRELESS GATEWAYS

With the Garmin Connex® family of flight connectivity solutions, you have an easy way to stream information between your tablet, smartphone or Garmin aviation portable and your helicopter’s avionics — making your device a true cockpit interface.

For example, with our Garmin Pilot™ app on your tablet or smartphone, it’s easy to create and preload your flight plan from the comfort of your home or office. Then, once you arrive at the airport, simply use Connex, via our Flight Stream 510 or 210 gateways, to wirelessly upload the information — waypoints, airway routings and all — into your helicopter’s GTN™ Xi, GTN™ or GNS™ series avionics during preflight. You save time. You get airborne more quickly.

Likewise, your Flight Stream also lets you access data from your avionics for display on your Apple® device for display in the Garmin Pilot, FltPlan and ForeFlight Mobile apps — as well as to your Garmin aera® 660/760 portable. So you can enhance the device’s map and flight displays with graphical weather, traffic and GPS position reference — virtually turning that device into an extra display in the cockpit¹.

And with a Flight Stream 510 — a patented multimedia card enabled with Wi-Fi® and BLUETOOTH® technology that installs easily into your GTN Xi, GTN or TXi flight display card slot — you get wireless database transfer to and from the avionics and Garmin Pilot app. Via Database Concierge, you can wirelessly download your new avionics databases to your Apple

mobile device at home, then upload them to your helicopter quickly at the airport. And if you have other compatible Garmin avionics, those new databases are synchronized behind the scenes; you even get immediate access to the departure, approach and arrival charts you need for your flight with chart streaming, even while those databases are still synchronizing. That’s data sharing with Garmin Flight Stream: It’s all about bringing greater efficiency and work-saving convenience to your cockpit management.

¹Capabilities such as GPS, attitude, weather, traffic and flight plan transfer are limited to the version of Flight Stream, the avionics installed in the aircraft as well as portable device. Compatibilities continue to grow with more apps and Garmin portables. Check the Flight Stream 510/210 web page’s “Supported Devices” tab for the latest feature and compatibility information.

Wi-Fi is a registered trademark of the Wi-Fi Alliance. Bluetooth is a registered trademark of Bluetooth SIG, Inc. and any use of such marks by Garmin is under license. Apple is a trademark of Apple Inc., registered in the U.S. and other countries.

SIRIUSXM® SATELLITE WEATHER

A great tool for helping helicopter pilots avoid inadvertent flight into adverse weather or low visibility conditions, SiriusXM Satellite Weather service is available with the installation of a Garmin GDL® 69 datalink receiver (SiriusXM subscription required). With this option, high-resolution NEXRAD imagery, METARs, TAFs, TFRs, winds aloft, echo tops, surface precipitation, lightning strikes, storm cell data and other weather updates for the entire U.S. can be accessed from your G500H TXi flight

display or GTN™ Xi series touchscreen. SiriusXM's geo-synchronous satellites over the east and west coasts of the continental U.S. enable this weather coverage to be accessed from any altitude. And for added entertainment value, there's also a user interface with the GDL 69A that offers inflight access to hundreds of channels of digital-quality SiriusXM Satellite Radio programming (additional service fee required).



GSR 56H GLOBAL WEATHER/VOICE/TEXT

In today's time-critical world, maintaining connectivity on the go has become a high priority for many companies. To help helicopter operators meet this need, Garmin has developed the GSR 56H, an Iridium-based satellite transceiver that's part of the Garmin ConnexT® ecosystem. Through a constellation of low-earth orbiting (LEO) satellites, this flight service, powered by the Iridium network, offers virtually seamless global coverage.

Your Garmin ConnexT datalink may be used to send and receive text messages using your smartphone, and even make calls through your headset, using your device's contact list. Furthermore, Garmin ConnexT enables a range of datalink services – including automatic position reporting and access to graphical weather, METARs, TAFs, winds aloft, PIREPs and more, on a worldwide basis.²



GARMIN ADS-B SOLUTIONS

You deserve to see tangible benefits from your ADS-B investment. That's why you'll want to equip with Garmin. We've taken a leading role in providing an affordable pathway to ADS-B compliance for the FAA's Next Generation Air Transportation System — as well as fulfilling the needs of other international ADS-B initiatives. These capable ADS-B “Out” solutions automatically transmit aircraft flight ID, position, altitude, velocity, climb/descent and heading information to provide precise dynamic reference to air traffic control, as well as to other ADS-B equipped aircraft sharing the airspace. Plus, they incorporate exclusive features to provide you with traffic and subscription-free weather information on a wide variety of Garmin displays, including G500H TXi flight displays, GTN™ 750Xi/650Xi series, GTN™ 750/650 series navigators and GNS™ 530W/430W navigators.

For example, TargetTrend™ relative motion display offers a faster, more intuitive way of judging target trajectories and closure rates in relation to your helicopter's flight path. Spoken audio alerts (“Traffic. Two o'clock. High. Two miles.”) also tell you where to look for potential threats, so you can stay “eyes out” to scan for traffic. Likewise, in the airport environment, our exclusive TerminalTraffic™ technology displays georeferenced ADS-B-equipped targets, including taxiing aircraft and ground service vehicles, on a SafeTaxi® surface diagram; ADS-B-equipped aircraft in-flight are easily distinguished from ground vehicles and taxiing aircraft, which are displayed using distinct colors and symbols. Plus, nuisance alerts are minimized and abbreviated while performing unique helicopter maneuvers such as hovering. And when paired with a GTN or GTN Xi series, they also offer On-scene mode — a traffic surveillance tool that minimizes nuisance traffic alerts in-flight when intentionally operating near other helicopters during operations such as electronic news gathering.

GTS™ SERIES ACTIVE TRAFFIC

For help in “seeing and avoiding” other aircraft in busy airspace, nothing beats having an extra set of electronic eyes in the cockpit. That's why smart helicopter pilots are looking to the Garmin GTS™ Series of traffic surveillance systems. Featuring exclusive Garmin CLEAR CAS™ (Correlated Location Enhanced ADS-B Receiver Collision Avoidance System) technology, these affordable TAS and TCAS I systems combine both active and passive surveillance, including dual link 978 and 1090 MHz ADS-B “In” from a GTX 345 all-in-one ADS-B transponder, to correlate target data and pinpoint traffic threats. Three distinct product configurations are available: GTS 800, GTS 825 and GTS 855. The GTS 800 system offers up to 22 nm of interrogation range, while the GTS 825 and GTS 855 TCAS I systems offer up to 40 nm and 80 nm of interrogation range, respectively. All three systems use surveillance data from nearby transponder-equipped aircraft to generate expanded audio alerts in an ATC-like spoken format:

“Traffic. 10 O'clock. High (or Low or Same Altitude). Two miles.” If bearing information is not available, “Traffic, No Bearing” is spoken. Passive surveillance of aircraft equipped with ADS-B “extended squitter” capability enables the system to more accurately derive the target aircraft's range, bearing and relative altitude. With traffic data graphically displayed on the GTN Xi, GTN and GNS series navigators and G500H TXi MFD (and also on the PFD with optional HSVT enabled), pilots can track specific flight trajectories of other aircraft in their vicinity – gaining a much clearer picture of their overall flight situation. Using familiar TCAS-defined symbology, up to 75 traffic targets can be tracked simultaneously on the GTS 825/855 (it's 45 on the GTS 800) — with up to 30 intruder threats being displayed at a time. What's more, with expanded voice alerts, pilots know where to look outside for called traffic — thus saving vital time when traffic is converging quickly.



Garmin traffic system alerting provides both visual and spoken audio advisories to help helicopter pilots maintain safe separation from other aircraft in busy airspace.



²See Garmin.com/ConnexT for special pricing on comprehensive rate plans that provide weather, voice and texting

GTX™ SERIES OF ALL-IN-ONE ADS-B TRANSPONDERS

The Garmin family of GTX series transponders brings ATC aircraft surveillance to new levels of precision, reliability and performance. The GTX 345 and GTX 335 transponders meet ADS-B “Out” compliance standards as certified 1090 MHz ADS-B solutions when paired with a compatible WAAS position source or upgraded to include an internal GPS position source, and, when paired with an active traffic system, they combine passive and active targets to display a comprehensive traffic picture available.

The GTX 345 all-in-one ADS-B transponder offers ADS-B “Out” with options for dual-link ADS-B “In” to display subscription-free weather and advanced ADS-B traffic. What’s more, the GTX 345 provides, via Bluetooth® and ConnexT wireless technology, ADS-B traffic, weather, GPS position data and back-up attitude information to Garmin aera 660/796/795 portables and Garmin Pilot™, FltPlan Go and ForeFlight Mobile apps. And the GTX 345 comes in an attractive size and form factor, making it easy to replace the outdated transponder in your panel. Remote-mount options are available.

The GTX 335 ADS-B transponder provides cost-effective ADS-B “Out” only. It also comes in an attractive size and form factor, making it easy to replace your old transponder, and remote-mount options are also available.



Combining an all solid-state transmitter with high-sensitivity receiver and digital signal processing, the Garmin GWX 75H offers superior weather detection technology compared to earlier magnetron-based radars. A variety of compatible MFDs, including GTN 750Xi series touchscreens, can double as your radar display – providing an overlay of the weather picture on your graphical moving map.

GWX™ 75H DIGITAL WEATHER RADAR

Meeting the tough environmental and vibration criteria for helicopter operations, the “H” version of the popular GWX 75H all-digital radar combines exceptional range and adjustable scanning profiles with precision target definition to bring you the best in real-time weather awareness. Pilot-adjustable horizontal scan angles of up to 120° enable you to focus scanning on the areas you want to watch, while vertical scanning helps you analyze storm tops, gradients and cell buildup at various altitudes. In addition, Weather Attenuated Color Highlight (WATCH™) technology can help identify areas beyond the radar’s capability that may contain even more hazardous areas of precipitation. With its advanced solid-state transmitter design eliminating the need for life-limited magnetron tubes, the Garmin GWX 75H comprises the very latest and most reliable technology in onboard weather radar. You can choose from 10", 12", or 18" antenna sizes to fit your requirements. What’s more, a feature called “Altitude Compensated Tilt” helps streamline cockpit workload by eliminating the need to reset the antenna tilt with any altitude change. And when interfaced with your aircraft’s analog gyro or AHRS system, the GWX 75H offers full stabilization to 30 degrees of pitch and roll. The radar’s lightweight 40-watt transmitter and high-sensitivity receiver combine to optimize the use of radar energy in weather detection. And unlike conventional magnetron tubes, which degenerate over time, the solid-state technology used in the GWX 75H will maintain a consistent weather picture over a much longer interval – with no periodic maintenance required. The net result: Longer life and higher efficiency with no compromise in radar performance. Better still, a handy Ground Mapping mode lets you use the GWX 75H to scan terrain features for visual navigation. And optional advanced features, enabled via software, include Doppler turbulence detection and ground clutter suppression.




Designed to work with the GI 205 standalone indicator, as well as compatible glass flight displays, the GRA 55 radar altimeter offers a complete and accurate height-above-terrain tracking solution at a value price. Its simple installation also eliminates the need for long lengths of antenna cabling, thus achieving further savings in system weight and cost.

GRA™ 55 RADAR ALTIMETER

Utilizing the same patented technology as our higher-end GRA 5500, the affordable GRA 55 system offers a great value in digital radar altimetry for most light helicopters. When paired with the stand-alone GI 205 Radar Altimeter Indicator, the GRA 55 provides a reliable, highly accurate radar altimeter solution without the need to equip your cockpit with a complete glass flight display system. However, if you do plan to install such a system – or if you already have one – the GRA 55 will also integrate with the G500H TXi and G500H flight displays, GTN Xi and GTN series touchscreens and other industry-standard compatible displays as well. Yet, no matter which display option you choose, the GRA 55 conveniently puts your AGL readout right where you need it for optimum visibility in high-workload landing situations. The GRA 55 is designed to work in a full range of demanding environments – allowing you to go from rough terrain to tree canopies, from sand to choppy water, while always knowing precisely how much room you have to maneuver.

Its flexible capabilities make it an optimal solution for those equipping for NVG operations. And thanks to patented self-testing technology that continuously monitors incoming data and system integrity, you can be assured that the altitude provided is accurate, even in low-visibility conditions. What's more, in most installations this self-testing technology substantially reduces the need for pilot input or interaction with the GRA 55 in any way. It simply provides a smooth, reliable, highly accurate altitude readout to help keep your AGL awareness as safe and dependable as you'd want it to be.



GSB™ 15 USB CHARGER

This dual-port USB hub can power and charge two electronic devices in the cockpit or cabin, including tablets and phones. So you can have the power to access flight plans, moving maps, charts, weather data, manuals and more on your mobile device – while your passengers can access entertainment, messaging and all types of productivity apps. The dual USB Type-A hub provides up to 18-watt output to each device, while the dual USB Type-C and USB Type-A/Type-C hubs offer the latest portables – including iPad Pro® tablets from 2018 or later – up to 27-watt output, plus USB Power Delivery technology to provide optimal power for each device. All slimline GSB 15 hubs measure just over 1.5" square and stand less than an inch deep. Two formats are available: either rear or side wiring connections to simplify installation in tight spots. The hub fits in a 1" hole and can be mounted into a standard instrument hole in the panel with an optional 2.25" or 3.125" adapter.




MISSION SUPPORT WITH GARMIN SERVICES

With industry-leading aviation support services from Garmin, helicopter pilots and fleet owners can now streamline their operations with a full suite of web-based logistics solutions. These offerings range from flight planning, filing and predeparture clearances to advanced trip support, flight tracking, airport and FBO information, weather briefings, navigation logs, safety/risk management tools and more.

FltPlan.com is one of the largest and most-trusted electronic flight-planning services in the U.S. The Garmin Pilot™ app provides additional integration and wireless connectivity. By creating a free FltPlan.com account and syncing it with Garmin Pilot, users can easily create flight plans and routings – then wirelessly transfer the data from their mobile device to their avionics, saving valuable time prior to any flight.

Once airborne, the moving map display on Garmin Pilot can support U.S. helicopter VFR overlays, as well as Gulf Coast VFR/IFR helicopter overlays to give pilots an added level of navigation support in the cockpit.

Other key Garmin support services include the FltPlan® SMS safety management system, which gives operators the tools to implement a formal SMS program that meets mandated FAA standards for their flight department, charter company or other commercial operation. This system integrates directly with the user's FltPlan.com account, seamlessly supporting a safety culture based on oversight and risk mitigation.



FltPlan SMS Safety Management System

Services such as our FltPlan safety management system help operators comply with documentation requirements while tracking and mitigating risks to their flight departments.



Garmin Pilot App

Bringing full-featured navigation, interactive mapping, flight planning and filing, automatic logging, database updating and more to compatible tablets and smartphones, the Garmin Pilot app is a helicopter pilot's ideal cockpit companion.

GARMIN HELICOPTER SYSTEM SPECIFICATIONS

G500H TXi FLIGHT DISPLAY	
Display Features	Electrical - GDU 700P
10.6" or 7" diagonal color LCD options RGB backlighting technology High resolution GDU 1060 - 1280 pixels (W) x 768 pixels (H) GDU 700P - 480 pixels (W) x 800 pixels (H) GDU 700L - 800 pixels (W) x 480 pixels (H) Direct sunlight readable Auto, manual, or lighting bus inputs for dimming Field upgradable software Available as 10.6" landscape, 7" portrait, or 7" landscape configurations	10-40 VDC, reverse polarity protected 42 watts typical System Architecture Position Source: Requires external SBAS/WAAS GPS, such as GTN 750Xi/650Xi, GTN 750/650 or GNS 430W/530W, or 430W/530W series unit Supported interfaces include: GDL 69/69A XM datalink weather, GRS 56 for global connectivity/WX; GTX 345, GTX 335 transponder; GDL 88 ADS-B datalink, GRA 55, GRA 5500 radar altimeters; various traffic sensors, and more Supported AHRS GRS 77, GSU 75H, GRS 79 Supported ADC GDC 74, GSU 75H, GDC 72 Electrical 10-40 VDC, reverse polarity protected 55 watts typical Environmental -20C to +55C operating temp -55C to +85C storage temp 2 degrees C per minute temp variation 95% at 50C humidity 35,000 ft max altitude Internal cooling, external cooling not required Certification Candidates STC via Approved Model List (AML) for popular makes/models TSO-C2d, TSO-C8e, TSO-C10b, TSO-C34e, TSO-C36e, TSO-C40c, TSO-C41d, TSO-C43c, TSO-C63d, TSO-C87a, TSO-C106, TSO-C110a, TSO-C113a, TSO-C118a, TSO-C147a, TSO-C157b, TSO-C165a, TSO-C195b, TSO-C198, TSO-C201 Physical - GDU 1060 Unit Size: 7.25 inches high 11.4 inches wide 3 inches deep 6.49 lbs. (without integral ADAHRS), 7.25 lbs. (with integrated ADAHRS) Physical - GDU 700P Unit Size: 7.25 inches high 5.5 inches wide 3 inches deep 3.99 lbs. (without integral ADAHRS), 4.45 lbs. (with integrated ADAHRS) Electrical - GDU 1060 10-40 VDC, reverse polarity protected 70 watts typical

GWX 75H DIGITAL WEATHER RADAR	
Physical	Electrical
Unit Size:	Base: 9.8 in (24.9 cm) x 8.3 in (21.082 cm) Depth: 7.076 in. (17.9 cm) Antenna: 10 in. or 12 in. diameter flat-plate
Unit Weight:	12-inch Antenna: 10.4 lbs. (4.72 kg) 10-inch Antenna: 10.2 lbs. (4.63 kg)
Environmental	
Operating temperature range:	-55 Degrees C to +70 Degrees C
Humidity:	95% non-condensing
Altitude Range:	-1,500 ft to 55,000 ft
TSO Compliance:	C63e, Class C, and A, B, D (Equipment is capable of Class A, B, and D when used with an enhanced feature software unlock card)
Environmental Category:	RTCA DO-160F
	Power Requirements: 28 VDC; 2.5A Transmitter Power: 40 Watts nominal, 36 Watts minimum Output Frequency Range: X-Band (9.3 to 9.5 GHz) Pulse Width: 2.23, 7.25, and 15.87 microseconds STC Logic: Extended STC: At all ranges 80 nm to 320 nm (Modifies targets from end of STC to maximum range) Stabilization: The radar always maintains a scan that is relative to the earth's horizon (subject to mechanical limits of the radar) Max. Altitude: 55,000 ft (unpressurized) Target Alert: Indicates the presence of heavy precipitation outside of selected range Interface: Garmin HSDB; ARINC 429/453

GTN 750Xi/650Xi SERIES AVIONICS	
Awareness	Transmitter TSO-C169a, Class 3, 4, 5 and 6; ETSO-2C169a Receiver TSO-C169a, Class C, E, H1 and H2 Stuck mic TSO-C128a Transmit Power: 10 watt or 16 watt (optional) GPS Receiver: 15 channel, including 3 GPS/WAAS/SBAS Acquisition Time: TTFF 1:45 minute typical (cold), 10sec reacquisition Update Rate: 5 per second Accuracy: <1.25 meter RMS horizontal; <2 meter vertical with WAAS Dynamics: 1000 knots max Nav Features: Navigation with flight plans and direct-to waypoints, Airway navigation, approach navigation using published approaches stored in flash memory, terminal navigation using DPs and STARs, closest point of flight plan, arrival and departure frequencies, turn advisories and arrival annunciations, electronic charts on GTN 750Xi series. NVIS-B compatible versions optionally available Planning Features: Trip and fuel planning, true air speed, density altitude, winds aloft, flight timers, trip statistics, sunrise and sunset, RAIM availability, advisory vertical navigation (VCALC) Interfaces: ARINC 429, ARINC 453/708, RS-232, HSDB, CDI/HSI, RMI (digital), altitude input (serial: Icarus, Shadin- Rosetta); fuel sensor, fuel / air data, radar altimeter, DME, GDL 69/69A XM, GTX 32/327/33/33D/330/330D, GTS 800/820/850, GDL 88/88D, GWX 68/70, GSR 56, G500/G600, GMA 35, L-3 Stormscope, L-3 Skywatch, Avidyne TAS, GAD 42, Flight Stream 210, and others. Map Datums: WGS-84
Physical	
Unit Size:	GTN 650Xi, 2.65" h x 6.25" w x 11.25" d (6.7 x 15.9 x 28.6 cm) GTN 750Xi, 6.00" h x 6.25" w x 11.25" d (15.2 x 15.9 x 28.6 cm) Depth is behind panel, including mounting rack and connectors
Unit Weight:	GTN 650Xi, 7.6 lb (3.46 kg); GTN 750Xi, 10.2 lb (4.63 kg) with mounting rack and connectors
Display:	Color TFT LCD; sunlight readable
Power:	11-33 VDC
Performance	
GPS:	TSO-C146e, Class 3, ETSO-C146e TSO-C40c, ETSO-2C40c
VOR:	TSO-C36e, ETSO-2C36f
LOC:	TSO-C34e, ETSO-2C34f
GS:	25 kHz and 8.33 kHz channel spacing
VHF COMM:	

GTS 800 Remote Processor	
Unit Size:	6.25"W x 2.7"H x 12.7"D (15.87 x 6.86 x 32.25 cm)
Weight:	11.3 lb (5.13 kg) LRU; Vert. Rack 1.35 lb (0.61 kg); Horiz. Rack 1.94 lb (0.88 Kg) excludes connectors
Temperature:	-55°C to +70°C
Operating Altitude:	To 55,000 ft
Power Input:	14 or 28 VDC 40 watts max. (GTS 800)
Cooling Input:	Integrated
Environmental Compliance:	RTCA DO-160F (contact dealer for installation options on specific aircraft)
Software Compliance:	RTCA DO-178B Level B
Hardware Compliance:	RTCA DO-254, Level B
TSO Compliance:	GTS 825 TAS: TSO-C147, TSO-C166b, RTCA DO-197A, RTCA DO-260B
GA 58 Directional Antenna	
Unit Size:	4.03"W x 2.97"H x 5.63"D (10.24 x 7.54 x 14.30 cm)
Weight:	0.82 lb (0.37 kg) with QMA connectors 0.85 lb (0.39 kg) with TNC connectors
GTS 825/855 Remote Processor	
Unit Size:	6.25"W x 3.42"H x 12.7"D (15.87 x 8.69 x 32.25 cm)
Weight:	11.3 lb (5.13 kg) LRU; Vert. Rack 1.05 lb (0.48 kg); Horiz. Rack 1.94 lb (0.88 Kg) excludes connectors
Temperature:	-55°C to +70°C

GTX 345 TRANSPONDER	
Physical	Transponder Features
Unit Size:	1.65" x 6.30" x 10.07" (42 x 160 x 256 mm)
Display type:	Digital
Weight:	3.1/3.2 lbs (1.41/1.45 kg) (unit, rack, connectors)
Voltage range:	14/28 VDC (18/20 W Max)
Transmit power:	1200 W minimum
Temperature:	-40° C to +70° C
Operating altitude:	To 55,000 ft (16,800 m)
Cooling input:	Not required
Environmental compliance (TSO Approved):	DO-160G
Software compliance (TSO Approved):	DO-178 Levels B, C, D, E
Hardware compliance (TSO Approved):	DO-254 Level C
TSO Compliance: (Approved)	TSO-C88b (w/opt. alt. encoder; TSO-C112e (Class 1, Level 2els; TSO-C154c (Class A1S); TSO-C157a (Class 1); TSO-C166b (Class A1S); TSO-C195a (Class C1,C2,C3,C4)
Mount type:	Panel
Transponder type:	Mode A/C, S and ES
Squawk code selection:	Push-button
Traffic Information Services (TIS) alerts compatible:	Yes
	Solid state transmitter: Yes (more efficient, longer life) Aural alerts: Yes Total Air Temperature (TAT): Yes Pressure altitude readout: Yes Altitude monitor function: 1200 W minimum Density altitude readout: Yes Built-in timers: Yes Automatic ALT/GND mode: Yes Wireless connectivity to portable device using Garmin Pilot, ForeFlight or compatible Garmin portable: Yes Subscription-free weather and traffic: Yes Internal AHRS (non-certified): Yes 1090 MHz ADS-B Out:Yes Dual-link 1090MHz and 978MHz UAT ADS-B In: Yes Displays on G500/G600, GTN 750Xi/650Xi series, GTN 650/750, GNS 430W/530W, and other: Yes Pressure altitude encoder module (mounts to connector backplate): Optional TAS/TCAS traffic integration with ADS-B In: Yes

GTX 335 TRANSPONDER	
Physical	Transponder Features
Unit Size:	1.65" x 6.30" x 10.07" (42 x 160 x 256 mm)
Display type:	Digital
Weight:	2.8/2.9 lbs (1.27/1.32 kg) (unit, rack, connectors)
Voltage range:	14/28 VDC (15/17 W Max)
Transmit power:	200 W minimum
Temperature:	-40° C to +70° C
Operating altitude:	To 55,000 ft (16,800 m)
Cooling input:	Not required
Environmental compliance (TSO Approved):	DO-160G
Software compliance (TSO Approved):	DO-178 Levels B, C, D
Hardware compliance (TSO Approved):	DO-254 Level C
TSO Compliance: (Approved)	TSO-C88b (w/opt. alt. encoder); TSO-C112e (Class 1, Level 2els); TSO-C166b (Class B1S)
Mount type:	Panel
Transponder type:	Mode A/C, S and ES
Squawk code selection:	Push-button
Traffic Information Services (TIS) alerts compatible:	Yes
	Solid state transmitter: Yes (more efficient, longer life) Aural alerts: Yes Total Air Temperature (TAT): Yes Pressure altitude readout: Yes Altitude monitor function: Yes Density altitude readout: Yes Built-in timers: Yes Automatic ALT/GND mode: Yes 1090 MHz ADS-B Out:Yes Built in GPS/WAAS receiver: Optional Displays on G500/G600, GTN 750Xi/650Xi series, GTN 650/750, GNS 430W/530W, and other: Yes Pressure altitude encoder module (mounts to connector backplate): Optional Night vision compatible: Optional

GI 275 ELECTRONIC FLIGHT INSTRUMENT	
Physical	Environmental
Unit Size:	Width: 3.25" (82.6 mm) Height: 3.25" (82.6 mm) Depth: 6.44" (163.6 mm) Depth with Connector: 7.40" (188.0 mm)
Weight:	1.9 lbs (0.86 kg) to 2.4 lbs (1.1 kg)
Active Display Size:	2.69" diameter
Display Resolution:	480 x 433 pixels
	Operating Voltage: 14/28 VDC Operating Temperature Range: -20°C to +55°C Altitude Range: -1,500 ft to 55,000 ft Other Specifications Wi-Fi® Class: 802.11b/g/n

GDL 69/69A DATALINK RECEIVER	
Features	Environmental
Delivers SiriusXM™ Satellite Weather to Garmin navigation systems; audio available with the GDL 69A (SiriusXM subscription required) Coverage at any altitude across continental U.S. Detailed NEXRAD imagery and textual and graphic METARS data Current reports on precipitation, lightning, winds aloft, echo tops, TFRs and more	Temperature: -55° C to +70° C (Operating) -55° C to +85° C (Storage) Humidity: 95% non-condensing Altitude range: -15,000 ft to +55,000 ft Power requirements: 9 to 33 VDC input 4.2 watts maximum Other Specifications Satellite receiver frequency: 2332.5 to 2345 MHz Downlink data rate: 38.4K bits per second Software Certification: RTCA DO-178B Level D Environmental Certification: RTCA DO-160D (Note: These are weights for GDL 69A, which is 0.14 lbs. heavier thanthe GDL 69)
Physical & Performance	
Unit Size:	6.15"W x 1.05"H x 7.20"D (15.62 x 2.66 x 18.28 cm) Includes mounting rack and connectors
Unit Weight:	1.86 lbs. (0.84 kg) unit, 3.06 lbs. (1.39 kg) unit and rack (Note: These are weights for GDL 69A, which is 0.14 lbs. heavier thanthe GDL 69)

GRA 55 RADAR ALTIMETER	
Physical	Altitude Range: -20 - 2550 ft AGL
Unit Size:	3.99"h x 3.02"w x 11.62"d (10.13 x 7.67 x 29.52 cm)
Unit Weight:	Includes mounting rack 3.5 lb. (1.59 kg) with mounting rack
Environmental	
Temperature:	-55° C to +85° C (Operating);
Altitude Range:	25,000 ft maximum
Power requirements:	14 or 28 VDC input; 13.75 watts maximum
Other Specifications	
Altitude Accuracy:	± 1.5 ft (3 - 100 ft AGL); ± 2° (> 100 - 2500 ft AGL)
	Altitude Alert Outputs Range: 0 - 2500 ft AGL Altitude Output Time Constant: 0.1 second maximum Transmitter Output: Frequency: 4.25 - 4.35 GHz "Gated" FMCW; Power: 1.0 W nominal Horizontal Velocity: 0 - 200 knots maximum Vertical Velocity: 20 ft/sec maximum (up to 100 ft AGL); 25 ft/sec maximum (above 100 ft AGL.) Pitch Angle: ± 20° maximum Roll Angle: ± 20° maximum (with published altitude accuracy limits); ± 20° to ± 30° (with ± 20 % altitude accuracy limits throughout entire altitude range)

GARMIN HELICOPTER SYSTEM SPECIFICATIONS

GFC 600H FLIGHT CONTROL SYSTEM			
Physical		Data Module	
Width (behind panel)	6.30" (16.0 cm)	Software Compliance	RTCA/DO-178B Level A, B, C, D, E
Bezel Width	6.25" (15.9 cm)		
Height (behind panel)	1.625" (4.1 cm)		
Bezel Height	1.65" (4.2 cm)		
Depth w/Air Data Module (behind panel)	9.61" (24.4 cm)	Hardware Compliance	RTCA/DO-254 Level A
Depth (behind panel) w/Connector Kit	9.61" (24.4 cm)		
Unit Weight w/out Connector Kit	2.19 lbs (0.99 kg)		
Weight, Unit w/Connector Kit and Air Data Module	2.91 lbs (1.32 kg)		
Install Rack Weight	0.34 lbs (0.15 kg)	Environmental Compliance	RTCA/DO-160F
Environmental			
Operating Temperature Range	-40° C to +70° C (-40° F to +158o F)		
Max Operating Altitude, GMC 605 only	55,000 ft		
Max Operating Altitude, GMC 605 w/Air Data Module	30,000 ft	Electrical	
Max Operating Airspeed, GMC 605 w/Air	300 kts		
Average Current Draw 14 VDC		0.53 A	
Maximum Current Draw 14 VDC		1.15 A	
Average Current Draw 28 VDC		0.27 A	
Maximum Current Draw 28 VDC		0.70 A	

GNC 215/GTR 205 VHF RADIO			
Navigation Radio Features		Database reverse lookup of frequencies providing station ID and frequency use (TWR, ATIS, etc.) with compatible GPS input or recent list populated by FIND	
(GNC 215 NAV/COMM)		Volume control bar graph display	
200-channel NAV with VOR/localizer and Glideslope receivers		Alphanumeric display of frequency types (ATIS, GRND, TWR, etc.)	
Built-in VOR/localizer converter		High-visibility alphanumeric LCD display	
Database lookup of frequencies using navaid ID		Transmit status indicator	
Reverse frequency lookup (with compatible GPS input)		Backlit keypad controls	
Standby NAV monitoring		Automatic and manual, pilot-selectable display intensity control	
VOR receiver displays to/from and radial.		Frequency memory and recall	
Digitally decoded OBS setting		Stores/recalls 20 user defined frequencies	
Sunlight-readable full alphanumeric display		Stores/recalls previous 20 frequencies used	
Automatic display of station ID by decoding Morse code		Squelch test function	
Interfaces to most CDI (w/resolver), HSI and autopilot systems		Stuck mic time-out	
NVIS-B enablement optionally available		NVIS-B-compatible versions available optionally	
Navigation Radio Performance		COMM Radio Performance	
VOR:	TSO-C40c, ETSO-2C40c	760 communication channels (w/ 25 kHz spacing); 2280 channels (w/ 8.33 kHz spacing)	
LOC:	TSO-C36e, ETSO-2C36f	Frequency range 118.000 to 136.992 MHz (w/ 8.33 kHz spacing)	
GS:	TSO-C34e, ETSO-2C34f	Transmit power: 10 or 16 watts output (by model)	
Accepts 9 to 33 VDC input		Input voltage range 9 to 33 VDC	
Physical		Transmit Power: 10 watt or 16 watt (optional)	
(GNC 215 NAV/COMM)		TSO Certification: Transmitter TSO-C169a, Class 3, 4, 5 and 6; ETSO-2C169a	
Bezel Size:	1.35" h x 6.25" w (3.43 x 15.88 cm)	Receiver TSO-C169a, Class C, E, H1 and H2	
Unit Weight:	2.3 lbs (1.0 kg) unit only; 3.1 lbs (1.4 kg) with mounting rack and connectors	Stuck mic TSO-C128a	
COMM Radio Features		Physical	
(GTR 205 and GNC 215)		(GTR 225 COMM)	
Active and standby flip-flop frequencies		Bezel Size: 1.35" h x 6.25" w (3.43 x 15.88 cm)	
One-touch 121.5 emergency channel tuning		Unit Weight: 2.2 lbs (1.0 kg) unit only; 2.8 lbs (1.3 kg) with mounting rack	
COMM frequency monitor function (listens to standby while monitoring the active)			
Recall of frequency from database by facility name and type			

GSR 56H SATELLITE TRANSCEIVER			
Physical		Other Specifications	
Unit Size:	2.31"W x 7.02"H x 12.96"D (5.87 x 17.83 x 32.91 cm)	Satellite receiver frequency: 1616 to 1626.5 MHz	
Unit Weight:	Depth is with connectors	Downlink data rate: 2.4 kilobits per second	
	2.45 lb.	Software Certification: RTCA DO-178B Level E	
Environmental		Environmental Certification: RTCA DO-160E	
Temperature:	-15° C to +70° C (Operating); -55° C to +85° C (Storage)		
Humidity:	95% non-condensing		
Altitude range:	-1,500 ft. to +55,000 ft		
Power requirements:	14 or 28 VDC input; 16 watts maximum		

GMA 350H DIGITAL AUDIO PANEL			
Features		Environmental	
Telligence voice command switching		Temperature: -45° C to +70° C (Operating)	
3-D Audio processing		Altitude range: to +55,000 ft. MSL unpressurized	
Advanced auto-squelch		Power Requirements: 11 to 33 VDC input	
3 comm radio support		Other Specifications	
Split comm mode		Transceiver inputs: 3	
Physical & Performance		Additional Receiver Inputs: 5	
Unit Size:	6.25"W x 1.30"H x 7.80"D (15.9 x 3.3 x 19.8 cm)	TSO Compliance: TSO-C50c, TSO-C35d	
Includes mounting rack and connectors			
Unit Weight:	2.4 lbs. (1.1 kg)		

GSR 56H SATELLITE TRANSCEIVER			
Physical		Power requirements: 14 or 28 VDC input; 16 watts maximum	
Unit Size:	2.31"W x 7.02"H x 12.96"D (5.87 x 17.83 x 32.91 cm)	Other Specifications	
Unit Weight:	Depth is with connectors	Satellite receiver frequency: 1616 to 1626.5 MHz	
	2.45 lb.	Downlink data rate: 2.4 kilobits per second	
Environmental		Software Certification: RTCA DO-178B Level E	
Temperature:	-15° C to +70° C (Operating); -55° C to +85° C (Storage)	Environmental Certification: RTCA DO-160E	
Humidity:	95% non-condensing		
Altitude range:	-1,500 ft. to +55,000 ft		





GARMIN INTERNATIONAL, INC.

Garmin.com/aviation

1200 East 151st Street, Olathe, KS 66062 p: 866.739.5687 f: 913.397.8282	GARMIN (EUROPE) LTD., Liberty House, Hounsdown Business Park, Southampton, Hampshire, SO40 9LR, U.K. p: +44 (0)87.0850.1243 f: +44 (0)23.8052.4004	GARMIN SINGAPORE PTE. LTD., 46 East Coast Road #10-03, Singapore 428766 p: 65.63480378 f: 65.63480278 e: avionics.asia@garmin.com
---	--	---

Wi-Fi is a registered trademark of the Wi-Fi Alliance.
©2024 Garmin Ltd. or its subsidiaries. All rights reserved
Prices, features and specifications subject to change without notice.



M02-10204-00 0224